

THORNE

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA

Log No. 56148
 Rec. 19
 Well No. _____
 Permit No. _____
 Do not fill in

Owner L. M. Lamb Driller S. R. McKinney & Son
 Address 740 West Palm, Redlands, Calif. Address 1042 S. Main Las Vegas, No. 45
 Location of well: SE 1/4 SW 1/4 Sec. 27, T.21 N/S, R.61 E, in Clark County
 or _____
 Water will be used for Domestic Total depth of well 200 ft.
 Size of drilled hole 12" to 50 ft, 10" to 300 Weight of casing per linear foot 10 guage
 Thickness of casing 10 guage Temp. of water _____
 Diameter and length of casing 8" I.D. to 200 ft.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 20 ft.
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well July 21, 1955 Date of completion of well July 25, 1955
 Type of well rig Bucyrus Erie 24 L. Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	sandy clay
5	28	23	caliche
28	55	27	sandy clay
55	83	28	gravelly clay little water
83	95	12	sandy clay
95	130	35	clay
130	150	20	sandy clay
150	194	44	gravelly clay
194	200	6	gravel water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 194 to 200 ft.

Other aquifers 55 to 83

First water at 55 feet.

Casing perforated
 from 160 to 200 ft.
80 100

Size of perforations
3/16" X 10"



