

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56163
 Rec. _____ 19____
 Well No. _____
 Permit No. _____
Do not fill in

Owner Bill Rosevear Driller S. R. McKinney & Son

Address 715 South 5th, Las Vegas, Nev. Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: SE 1/4 SW 1/4 Sec. 27, T. 21N/S, R. 61 E, in Clark County

or SE 1/4 of NW 1/4 of SE 1/4 of S. 1/4 of Section 27, Twp. 21, Range 61

Water will be used for Domestic Total depth of well 175 ft.

Size of drilled hole 12" to 50 ft, 10" to 175 Weight of casing per linear foot 10 guage

Thickness of casing 10 guage Temp. of water _____

Diameter and length of casing 175 ft. of 3" I.D.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 30 ft.

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well Feb. 5, 1955 Date of completion of well Feb. 8, 1955

Type of well rig 72 Speed Star Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	15	15	caliche sandy soft
15	30	15	hard caliche
30	40	10	clay
40	55	15	caliche water
55	70	15	sand
70	80	10	sand and gravel water
80	95	15	clay
95	115	20	caliche water
115	140	25	soft sandy clay
140	165	25	sand and gravel water
165	175	10	sandy clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 140 to 165 ft.

Other aquifers 95 to 115

40
First water at _____ feet.

Casing perforated
from 100 to 175 ft.

Size of perforations
3/16" X 10"



