

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

56175

Log No. \_\_\_\_\_  
 Rec. \_\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

1

Do not fill in

Owner Jack T. Bolcher Driller Effinger Bros.  
 Address Box 733 Las Vegas, Nevada Address 1001 Artesia Way Lic. No. \_\_\_\_\_  
 Location of well: \_\_\_\_\_ 1/4 \_\_\_\_\_ 1/4 Sec. \_\_\_\_\_, T. \_\_\_\_\_ N/S, R. \_\_\_\_\_ E, in \_\_\_\_\_ County  
 or Tract #4 Section 28 T21S R61E  
 Water will be used for Domestic Total depth of well 150 feet  
 Size of drilled hole 12 inch Weight of casing per linear foot 12.06 lbs.  
 Thickness of casing 10 Gauge Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8 5/8"OD 150 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 22'7" from top of casing  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well April 8, 1955 Date of completion of well April 13, 1955  
 Type of well rig "71 Speed Star"

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	0		Gyp	
0	0		Cement Gravel	
0	0		Gravel	Chief aquifer (water-bearing formation)
0	0		Cement Gravel	from <u>142</u> to <u>145</u> ft.
0	0		Gravel	
0	0		Cement Gravel	Other aquifers <u>121-124</u>
0	0		White Clay	<u>56-62</u>
0	0		Gravel (Water)	
0	0		Cement Gravel	
0	0		Red Clay	
0	0		Cement Gravel	
0	0		Red Clay	
0	0		Cement Gravel	
0	0		Gravel (Water)	First water at <u>32</u> feet.
0	0		Cement Gravel	
0	0		Red Clay	
0	0		Sandstone	Casing perforated
0	0		Red Clay	from <u>50</u> to <u>150</u> ft.
0	0		Sandstone	
0	0		Red Sand (Water)	Size of perforations
0	0		Red Clay	<u>1/8" X 12"</u>
0	0		Sandstone	
0	0		Limestone (Water)	
0	0		Sticky Clay	

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
3 5/8" OD	0	150	150	Cemented from 0 to 50 feet Graveled packed from 50 to 150 feet. 3 yards of pea gravel 1 1/2 yards of cement

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

---



---



---



---



---



---

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Effinger Bros.  
Well Driller

By A. F. Effinger  
License No. 205

Dated April 13, 1955

(Not to be filled in by Driller)

---



---



---



---



---



---



---



---



---



---