WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56216
Rec. 19
Well No. 28
Permit No. .....
Do not fill in

Owner Harvey N. Peterson
P. O. Box 706
Address Las Vegas, Nevada

Driller Charlie Cribbs
Address Las Vegas, Nevada Lic. No. 70

Location of well: SW 1/4 NW 1/4 Sec. 28, T. 21 N/S, R. 61 E, in CLARK County
or T 21 S - R 61 E, Sec 28 - W 1/2 - SW 1/4 - SW - 1/4 - NW - 1/4 = total 1 1/4 Acres

Water will be used for Domestic Total depth of well 90

Size of drilled hole 10 Inch Weight of casing per linear foot 5 Lbs

Thickness of casing 1/16 Temp. of water

Diameter and length of casing 8 Inch OD 60 Ft. Long
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 20 Ft.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well June 7, 1951 Date of completion of well June 14, 1951

Type of well rig Spudder Bucyrus Erie 22W

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Sandy Top Soil
2	20	18	Hard Lime Rock
20	30	10	White Clay
30	31	1	Gravel Water
31	50	19	White Clay
50	52	2	Very little gravel
52	80	28	White Clay
80	83	3	Gravel Water
83	90	7	Red Clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 80 to 83 ft.

Other aquifers

First water at 30 feet.

Casing perforated

from ..... to ..... ft.

Size of perforations

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
80D	0	60	60	One and one Half yards of Grouting

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Charlie Cribbs
Well Driller

By Charlie Cribbs

License No. 70

Dated June 14, 1951

(Not to be filled in by Driller)