

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. insp. 56220
 Rec. 6/20 1955
 Well No. _____
 Permit No. _____
 Do not fill in

Owner Elnor V. Price Driller S. R. McKinney & Son
 Address General Delivery, Caliente, Nev. Address 1042 So. Main, L.V. Lic. No. 45
 Location of well: SW 1/4 NE 1/4 Sec. 26, T. 21 N/S, R. 61 E, in Clark County
 or W 1/2 of SW 1/4 of NE 1/4 of SW 1/4 of NW 1/4 of Sec. 26, Twp. 21, Range 61
 Water will be used for Domestic Total depth of well 110'
 Size of drilled hole 12" to 50' 10" to 150' Weight of casing per linear foot 10 Gauge
 Thickness of casing 10 Gauge Temp. of water _____
 Diameter and length of casing 6" I.D. to 150'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 28'
 If flowing well describe control works _____
(Type and size of valve, etc.)
 Date of commencement of well June 2, 1955 Date of completion of well June 5, 1955
 Type of well rig 72 Speed Star, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	14	14	Gravel
14	18	4	Caliche
18	21	3	Gravel
21	22	1	Caliche
22	26	4	Caliche
26	29	3	White Clay
29	34	5	Brown Sandy clay
34	36	2	Brown Sand water
36	46	10	Brown Clay
46	48	2	Brown Sand water
48	74	26	Brown Clay
74	78	4	Gravel water
78	86	8	Brown Clay
86	89	3	Brown Sand water
89	107	18	Brown Clay
107	111	4	Gravel water
111	137	26	Brown Clay
137	141	4	Gravel water
141	150	9	Brown Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 137 to 141 ft.

107' to 111'

Other aquifers 86' to 89'

74' to 78'

46' to 48'

34' to 36'

First water at 34 feet.

Casing perforated

from 70 to 150 ft.

3/16" x 10" Size of perforations

