WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 56229
Permit No.
Basin 082

NOTICE OF INTENT NO. 31574

1. OWNER Lex Simpson
MAILING ADDRESS 2600 Kinney Lane
Reno, Nevada 89511

ADDRESS AT WELL LOCATION 2600 Kinney Lane
Reno, Nevada 89511

2. LOCATION SW ¼ NE ¼ Sec. 2 T 18 N/S R 19 EAST WASHOE County
PERMIT NO. Issued by Water Resources | 41-253-04 Parcel No. | Cottonwood Estates Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [X] Other mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Brown Clay & brown sand		0	30	
Brown Clay & multi colored gravels		30	220	
Multi colored volcanic rock & gray clay		220	225	
Gray clay & granite		225	295	
Gray clay & multi colored gravels		295	335	
Gray clay & multi colored course sand		335	395	
T.D 395',				

Date started June 13, 19 96
Date completed June 21, 19 96

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
30+		10

8. WELL CONSTRUCTION
Depth Drilled 395 Feet Depth Cased 395 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 5/8 Inches		0 Feet	395 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.92	.188	1½	395

Perforations:
Type perforation Houston Stainless Screen
Size perforation .030 Slot
From 195 feet to 205 feet
From feet to feet
From 385 feet to 395 feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 100
Placement Method: [X] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 395 feet to 100 feet

9. WATER LEVEL
Static water level +1 feet below land surface
Artesian flow YES 5 G.P.M. 10 P.S.I.
Water temperature COLD °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name A.S.A.P. Pump & Well Service Inc. (Contractor)
Address 1800½ Frazer Avenue (Contractor)
Sparks, Nevada 89431

Nevada contractor's license number issued by the State Contractor's Board 35387-A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1509T-1

Signed Larry Welch (By driller performing actual drilling on site or contractor)
Date July 19, 1996

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627