


WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA

Log No. 56244
 Rec. 19
 Well No. _____
 Permit No. _____
 Do not fill in



Owner Ethel Soss Rorsman Driller McKesson & Stock
 Address 11634 San Vincente Blvd, Los Angeles Calif. Address 1629 N. Main N., Las Vegas Nevada Lic. No. 200
 Location of well: 1/4 1/4 Sec., T. N/S, R. E, in Clark County
 or Sec. 28 T21 So., R66E Lot #1 Mt., Diablo Meridian
 Water will be used for Domestic Total depth of well 125
 Size of drilled hole 8 inch Weight of casing per linear foot 11.7
 Thickness of casing 10 Gauge Temp. of water Coal
 Diameter and length of casing 8 inch 125 feet long
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 35 feet
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well June 8 1955 Date of completion of well June 11 1955
 Type of well rig Keystone # 50

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Gravel
2	9	7	Caliche
9	32	23	Cemented Gravel
32	52	20	Red Mud and Gravel
52	55	3	Cemented Gravel
55	67	12	Clay & Gravel (water)
67	69	2	Cemented Gravel
69	125	56	Clay & Gravel

Water-bearing Formation, Casing Perforations, Etc.
 Chief aquifer (water-bearing formation)
 from 55 to 67 ft.
 Other aquifers _____
 First water at 55 feet.
 Casing perforated
 from 50 to 125 ft.
 Size of perforations
1/2 inch, 6 inches long
staggered around casing

