WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56272
Rec. 19
Well No. .....
Permit No. 15970
Do not fill in

Permit issued for .02 CFS

Owner: Chas & Geo Wright — Driller: O A Effinger

Address: Lot 39-40 — Address: Las Vegas Nev — Lic. No. 63

Location of well: NW1/4 SW1/4 Sec. 28, T. 21 N/S, R. 61 E, in Clark County

or 2A High way

Water will be used for: Domestic — Total depth of well: 115 FT

Size of drilled hole: 8 in — Weight of casing per linear foot: 20#

Thickness of casing: 5/16 — Temp. of water: .....

Diameter and length of casing: 8 in I.D. 50 FT
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: .....

If nonflowing well give depth of standing water from surface: 21 FT

If flowing well describe control works: .....
(Type and size of valve, etc.)

Date of commencement of well: May 11-1953 — Date of completion of well: May 16-1953

Type of well rig: 71 ST

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Sand
3	9	6	Gravel
9	13	4	Clay (Yellow)
13	27	14	Cement Gravel
27	34	7	Sand 1st water
34	52	18	Cement Gravel
52	58	6	Red Clay
58	67	9	Cement Gravel
67	71	4	Yellow Clay
71	89	18	Cement Gravel
89	96	7	Yellow Clay
96	105	9	Gravel (water)
105	115	10	Yellow Sandy Clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 96 to 105 ft.

Other aquifers .....

First water at 34 feet.

Casing perforated

from ..... to ..... ft.

Size of perforations .....

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8	0	50	50	Cemented

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Bert Hawthorne
Well Driller

By

License No. 63

Dated June 18, 1953

(Not to be filled in by Driller)