

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56305  
 Rec. 19  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Frank L. Howard Driller W. J. Mason  
 Address 2012 South 10th Street Address 1727 Santa Paula Drive  
Las Vegas, Nevada Las Vegas, Nevada Lic. No. 195

Location of well: 1/4 1/4 Sec., T. N/S, R. E, in \_\_\_\_\_ County  
 or Lot # 7, Tract # 1, Section 32, Twp. 21 South Range 61 E. M. D. M.

Water will be used for Domestic Total depth of well 160

Size of drilled hole 10 inch Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water ~~74~~ 74 deg.

Diameter and length of casing 160 feet of 6 inch  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 90 feet

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well April 1st, 1955 Date of completion of well April 20th, 1955

Type of well rig Rotary

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	90	90	Clay, sand & gravel
90	115	25	Sand & gravel
115	160	45	Sand, gravel & streaks of Clay

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 90 to 115 ft.  
 Other aquifers 140 to 160

---

First water at 90 feet.

---

Casing perforated  
 from 90 to 115 ft.  
140 160

---

Size of perforations  
1/16

