WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56319
Rec. 19
Well No.
Permit No.
Do not fill in

Owner Jimmey Ray Driller S. R. McKinney & Son

Address 1385 Bunena Vista, Palm Springs Calif. Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: NW ¼ SE¼ Sec. 32, T. 21 N/S, R 61 E, in Clark County

or

Water will be used for Domestic Total depth of well 170 ft.

Size of drilled hole 10" to 170 ft Weight of casing per linear foot 10 Guage

Thickness of casing 10 guage Temp. of water

Diameter and length of casing 8" O.D. to 170 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface -120 ft.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Jan 14, 1954 Date of completion of well Jan 22, 1954

Type of well rig Bucyrus Erie 24, I, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Surface soil
5	60	55	Gravel
60	65	5	clay
65	75	10	cemented gravel
75	145	70	red sandy clay
145	150	5	gravel water
150	165	15	red sand
165	170	5	gravel water

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 165 to 170 ft.

Other aquifers 145 to 150

First water at 145 feet.

Casing perforated

from 130 to 170 ft.

Size of perforations

1/8" X 12"

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
			MP. 1 1/2 nipple

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8" O.D.	0	170	170	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailed 20 G.P.M. from 150 ft.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed L. R. McKinney & Son
Well Driller

By M. E. McKinney

License No. 45

Dated Feb 17, 1954

(Not to be filled in by Driller)

1. not in use - cap welded on casing