WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56330
Rec. ..... 19.....
Well No. .....
Permit No. .....
Do not fill in

Owner: Hugh B. Wilde
Address: 2012 South 10th Street, Las Vegas, Nevada

Driller: W. J. Mason
Address: 1727 Santa Paula Dr., Las Vegas, Nevada Lic. No. 195

Location of well: ....¼....¼ Sec...., T....N/S, R....E, in.....County
or S½SE¼SW¼SE¼SE¼ Section 32, Twp. 21 South Range 61 E. M. D. M.

Water will be used for: Domestic
Total depth of well: 160

Size of drilled hole: 10 g inch
Weight of casing per linear foot: 10 gauge

Thickness of casing: 10 gauge
Temp. of water: 74 deg.

Diameter and length of casing: 160 feet of 6 inch
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: .....

If nonflowing well give depth of standing water from surface: 90 feet

If flowing well describe control works: .....
(Type and size of valve, etc.)

Date of commencement of well: April 1st, 1955
Date of completion of well: April 20th, 1955

Type of well rig: Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	90	90	Clay, sand & gravel
90	115	25	Sand & gravel
115	160	45	Sand, gravel & streaks of Clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 90 to 115 ft.

Other aquifers: 140 to 160

First water at 90 feet.

Casing perforated
from 90 to 115 ft.
140 160

Size of perforations
1/16

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	160	160	50 feet of Cement

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

20 gallons per minute by bailer test

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed William S. Mary
Well Driller

By.....

License No. 195

Dated June 14th, 19 55

(Not to be filled in by Driller)