

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 56348  
 Res. No. \_\_\_\_\_ 19  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Robert Farney & Maikle Driller S. R. McKinney & Son

Address Box 1871, Las Vegas Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: 1/4 SE 1/4 Sec. 21., T. 20N/S, R. 62E, in Clark County  
 or \_\_\_\_\_

Water will be used for domestic Total depth of well 100 ft.

Size of drilled hole 10" to 30 ft, 8" to 100 ft. Weight of casing per linear foot 18 lb.

Thickness of casing 3/16" Temp. of water \_\_\_\_\_

Diameter and length of casing 8" O.D. to 40 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 40 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well June 12, 1953 Date of completion of well June 12, 1953

Type of well rig Macyrus Erie 24 L, Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	topsoil
3	42	39	brown clay
42	45	3	brown sand water
45	65	20	red sandy clay
65	70	5	red sand water
70	85	15	red sandy clay
85	90	5	red sand water
90	100	10	red clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 85 to 90 ft.

Other aquifers 65 to 70

42 to 45

First water at 42 feet.

Casing perforated

from None to \_\_\_\_\_ ft.

Size of perforations



