


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 56357
 Rec. 19...
 Well No.
 Permit No.
 Do not fill in.



Owner Mr. & Mrs. Griggs (Maude & V.V.) Driller Douglas M. Slagle
 Address 1932 Betty, Las Vegas Address 4518 E. Vegas Vally Dr. Lic. No. 137
 Location of well: NE 1/4 SW 1/4 Sec. 21, T. 20S N/S, R. 7SE, in Clark County
 or corner of Betty & Meikle Ln.

Water will be used for Domestic Total depth of well 260 ft.

Size of drilled hole 8 1/2 inch I2 to I4 inches Weight of casing per linear foot Approx. 16.2 #

Thickness of casing 10 Gage Temp. of water cool

Diameter and length of casing 8" X 260 Ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure --

If nonflowing well give depth of standing water from surface

If flowing well describe control works ---
(Type and size of valve, etc.)

Date of commencement of well August 1964 Date of completion of well August 1964

Type of well rig Bucyrus-Erie 29W

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, etc.
0-16	16	16	fine Fill (brn.)	
16	20	4	gravel (no Water)	
20	40	20	light brown Clay	
40	65	25	cream colored Clay	
65	73	8	white Clay	
* 73	78	5	water & gravel	Chief aquifer (water-bearing formation) from <u>235</u> to <u>254</u> ft.
78	110	32	white Clay-sand	Other aquifers <u>73-78</u>
110	135	25	white Clay	<u>136-139, 175-180</u>
135	136	1	Rock	<u>235 to 254</u>
* 136	139	3	gravel & water	
139	175	36	white Clay	
* 175	180	5	water (not much)	
180	200	20	white clay & Rock	
200	235	35	white Clay	
* 235	254	19	water & Clay	First water at <u>73-78</u> feet.
254	260	6	light brown Clay	Casing perforated from <u>60</u> to <u>260</u> ft.

Size of perforations

1/8" x 12"

