

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56477  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Wm. Miekle Driller S. R. McKinney & Son

Address Box 1871, Las Vegas, Nevada Address 1042 S. Main, Las Vegas Est. No. 45

Location of well S. 1/4, 1/4, Sec. 21, T. 20N/S, R. 6E, in Clark County  
or Miekle Manor #2 lot 304

Water will be used for D. & I. Total depth of well 75

Size of drilled hole 8" to 75 ft. Weight of casing per linear foot 10 guage

Thickness of casing 10 Guage Temp. of water \_\_\_\_\_

Diameter and length of casing 8" O.D. to 20 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 43 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well April 9, 1952 Date of completion of well April 9, 1952

Type of well rig Bucyrus Erie 24 L, Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	Top soil
6	10	4	Gravel and clay
10	43	33	Brown sandy clay
43	46	3	Sand Water
46	60	14	Brown sandy clay
60	65	5	Sand and gravel, Water
65	75	10	White clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 60 to 65 ft.

Other aquifers 43 to 46

First water at 43 ft feet.

Casing perforated  
 None  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations

