

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56494  
 Recd. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*



Owner Meikle and White Corbell Driller S. R. McKinney & Son

Address Box 1871, Las Vegas Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: SE <sup>SW</sup> 1/4 SE 1/4 Sec. 21., T. 20N/S, R. 62E, in Clark County  
 or \_\_\_\_\_

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 10" to 55 ft., 8" to 100 ft Weight of casing per linear foot 10 Gauge

Thickness of casing 10 gauge Temp. of water \_\_\_\_\_

Diameter and length of casing 8" O.D. to 60 ft.  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 35 ft.

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well Nov 10, 1953 Date of completion of well Nov 11, 1953

Type of well rig Bucyrus Erie 24 L. Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Top soil
8	30	22	Brown clay
30	38	8	gravel dry
38	55	17	gravel <del>dry</del> Water
55	60	5	red sand water
60	75	15	red sandy clay
75	80	5	red sand water
80	95	15	red sandy clay
95	100	5	red sand water

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 95 to 100 ft.

Other aquifers 75 to 80

---

First water at 38 feet.

Casing perforated  
 from none to \_\_\_\_\_ ft.

Size of perforations \_\_\_\_\_

