

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56508  
 Rec. 19  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Harvey Dickerson Driller McGarvie Plumbing & Welding  
 Address County of Clark Address Las Vegas, Nevada Lic. No. 132  
 Location of well: NE 1/4 SW 1/4 Sec. 35, T21sN/S, R61 E, in County of Clark County  
 or M.D.M.  
 Water will be used for Domestic Total depth of well 175'  
 Size of drilled hole 8" Weight of casing per linear foot 8" by 10 gauge  
 Thickness of casing 8" by 10 gauge Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" BY 10 gauge  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 26'  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well \_\_\_\_\_ Date of completion of well March 17, 1955  
 Type of well rig cable

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	18	18	white clay with caliche
18	24	6	red sandy clay
24	26	2	hard caliche shell
26	55	29	red clay
55	60	5	hard sandstone
60	110	50	red sandy clay
110	112	2	hard shell
112	175	63	red sandy clay with hard reefs
			water at 26'

Water-bearing Formation, Casing Perforations, Etc.  
26' down to depth  
 Chief aquifer (water-bearing formation)  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.  
 Other aquifers \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 First water at 26' feet.  
 Casing perforated  
 from 60 to 100 ft.  
 Size of perforations  
1/8" x 6" slots  
5 rows with  
24" centers

