


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

56514

Log No. 56514
 Rec. 19
 Well No. 
 Permit No. _____
Do not fill in

Owner Felix Garcia Driller S.R. McKinney & Son
 Address 3211 South 5th St., Las Vegas, Nev. Address 1042 So. Main Street Lic. No. 45
 Location of well: NE 1/4 Sec. 35, T.21 N/S, R.61 E, in Clark County
 or SW 1/4 of th SW, NE 1/4, SW 1/4 of Section 35, Twp. 21, Range 61
 Water will be used for Domestic Total depth of well 120'
 Size of drilled hole 12" to 50, 10" to 120' Weight of casing per linear foot 10 Gauge
 Thickness of casing 10 Gauge Temp. of water _____
 Diameter and length of casing 6" I.D. to 120'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 12'
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well May 21, 1955 Date of completion of well May 23, 1955
 Type of well rig Bucyrus Erie 24-L Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Sand
2	8	6	caliche
8	11	3	White clay
11	16	5	caliche water
16	26	10	red sandy clay
26	28	2	red sandstone
28	42	14	red sand water
42	55	13	red sand & gravel water
55	74	19	Brown sandy clay
74	78	4	Gravel water
78	87	9	red sand & gravel water
87	112	25	red sand
112	115	3	Gravel water
115	120	5	red sandy clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 112 to 115 ft.

Other aquifers 78' to 87'

74' to 78'

42' to 45'

28' to 42'

11' to 16'

First water at 111 feet.

Casing perforated

from 60 to 120 ft.

Size of perforations
3/16" x 10"

