

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

56517

Log No. _____
 Rec. _____
 Well No. _____
 Permit No. _____

Do not fill in

Owner Van Hanley Driller S. R. McKinney & Son

Address ht. 1, Box 106A, Paradise Valley Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: Sunset Rd. Las Vegas, Nevada County _____

or SW 1/4 NE 1/4 Sec. 35, T. 21 N/S, R. 61 E, in Clark

or SW 1/4 of SE 1/4 of SW 1/4 of NE 1/4 of Section 35, Twp. 21 Range 61 East

Water will be used for Domestic Total depth of well 130 ft.

Size of drilled hole 12" to 50 ft., 10" to 130 Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water _____

Diameter and length of casing 8" I.D. to 130 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 38 ft.

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well April 1, 1955 Date of completion of well April 3, 1955

Type of well rig Bucyrus Erie, 24 L, Spud or

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	9	9	sand and gravel
9	33	24	brown clay
33	36	3	red sand water
36	41	5	red clay
41	47	6	brown sand water
47	50	3	brown clay
50	55	5	5 brown sand
55	64	9	brown clay
64	69	5	red sand water very little
69	76	7	red clay
76	81	5	red sand water very little
81	90	9	red clay
90	95	5	red sand water
95	108	13	red clay
108	113	5	red sand water
113	126	13	red clay
126	130	4	red sand water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 126 to 130 ft.

Other aquifers 108 to 113
90 to 95

First water at 33 feet.

Casing perforated
 from 90 to 130 ft.

Size of perforations
3/16" I 10"

