

See copy

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56528
 Rec. 6/23 1955
 Well No. _____
 Permit No. _____
Do not fill in

Owner Edward R. Johnston Driller S.R. McKinney & Son
 Address 4607 Baxter Place, Las Vegas, Nev Address 1042 So. Main, L.V. Lic. No. 45
 Location of well: SE 1/4 SW 1/4 Sec. 35, T. 21 N/S, R. 61 E, in Clark County
 or SE 1/4 of NE 1/4 of SE 1/4 of SW 1/4 of Sec. 35, Twp. 21, Range 61
 Water will be used for Domestic Total depth of well 130'
 Size of drilled hole 12" to 50', 10" to 130' Weight of casing per linear foot 10 Gauge
 Thickness of casing 10 Gauge Temp. of water _____
 Diameter and length of casing 8" I.D. to 130'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 20'
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well June 18, 1955 Date of completion of well June 20, 1955
 Type of well rig Hucyrus Erie 24L Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	5	5	Soil & Clay	Chief aquifer (water-bearing formation) from <u>122</u> to <u>130</u> ft. Other aquifers <u>105' to 108'</u> <u>25' to 35'</u> First water at <u>25</u> feet. Casing perforated from <u>90</u> to <u>130</u> ft. Size of perforations <u>3/16" x 10"</u>
5	25	20	Caliche	
25	35	10	Clay & Gravel water	
35	105	70	Shaly sandstone sandy clay	
105	108	3	Clay & Gravel water	
108	122	14	Clay	
122	130	8	Clay & Gravel water	

