

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. <b>56559</b>
Rec. _____ 19__
Well No. _____
Permit No. _____

Do not fill in

Owner ROY J PFLEEGER Driller Charlie Cribbs

Address 106 E. Bananza Road Lasvegas Address Gen. Del. Lasvegas Lic. No. 70  
Clark

Location of well: 1/4 Sec. \_\_\_\_\_, T. N/S, R. E, in \_\_\_\_\_ County  
 or SE 1/4 NW 1/4 NW 1/4 SW 1/4 Sec 35 T 21S R 61 E

Water will be used for Domestic Total depth of well 107 Ft.

Size of drilled hole 12 in to 50 ft 10 in to 107 Weight of casing per linear foot 10

Thickness of casing 10 Gauge Temp. of water \_\_\_\_\_

Diameter and length of casing 8 5/8 OD.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 8 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Nov 3 Date of completion of well Nov. 6

Type of well rig SPUDDER

LOG OF FORMATIONS				Water-bearing Formation, Casing Perforations, Etc.
From feet	To feet	Thickness feet	Type of material	
00	8	8	Silt sand & gravel	
8	20	12	Colechie Hard (Water)	Chief aquifer (water-bearing formation)
20	60	40	Brown Clay	
60	65	5	Gravel sand and (Water)	from 95 to 98 ft.
65	95	30	Streaks of rock & clay 2 & 3 Ft. thick	60 to 65 20
95	98	3	Gravel 63 Water	Other aquifers _____
98	107	12	Red clay	
			Total Depth 107	
				First water at <u>20</u> feet.
				Casing perforated from <u>60</u> to <u>100</u> ft.
				Size of perforations <u>1/4 X 6 in</u>

