

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. **56577**  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner M. S. Staley Driller S. B. McKinney & Son  
 Address 611 Biltmore, Las Vegas, Nevada Address 1042 S. Main Las Vegas Lic. No. 45  
 Location of well: SW 1/4 NE 1/4 Sec. 35, T. 21N/S, R. 61E, in Clark County  
 or SE 1/4 of SW 1/4 of SW 1/4 of NE 1/4 of section 35, Twp. 21, Range 61 E.  
 Water will be used for Domestic Total depth of well 135 ft.  
 Size of drilled hole 12" to 50 ft, 10" to 135 Weight of casing per linear foot 28 lb.  
 Thickness of casing 1/4" Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" I.D. to 135 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 20 ft.  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well Feb. 11, 1955 Date of completion of well Feb. 14, 1955  
 Type of well rig 71 Speed Star Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	soil and clay
5	20	15	caliche
20	40	20	sandy clay water
40	50	10	clay and gravel
50	80	30	sandy clay water
80	120	40	<del>clay and gravel</del> sandy clay
120	125	5	clay and gravel
125	135	10	gravel water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 125 to 135 ft.

Other aquifers 50 to 80

First water at 20 feet.

Casing perforated from 90 to 135 ft.

Size of perforations 3/16" & 10"



