


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56591  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*



Owner Bernard C. Fatten Driller S. R. McKinney & Son

Address 1762 Nellis Blvd., Las Vegas, Nev. Address 1042 S. Main Las Vegas No. 45

Location of well: SW 1/4 SW 1/4 Sec 21, T20N/S, R62E, in Clark County

or \_\_\_\_\_

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 13" to 50 ft., 10" to 100 Weight of casing per linear foot 20 lb.

Thickness of casing 1/4" Temp. of water \_\_\_\_\_

Diameter and length of casing 8" I.D. to 100 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 39 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well July 3, 1956 Date of completion of well July 5, 1956

Type of well rig Bucyrus Erie 24 L. Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	40	40	Red clay
40	53	13	sand and gravel water
53	65	12	brown sandy clay
65	75	10	brown sand water
75	87	12	white clay
87	95	8	white sand water
95	100	5	white clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 87 to 95 ft.

Other aquifers 65 to 75

40 to 53

First water at 40 feet.

Casing perforated

from 60 to 100 ft.

Size of perforations

3/16" x 10"



