

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 56592  
 Rec. 19  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Floyd C. Williams Driller Effinger Drill & Pump Serv.

Address Bruce & Patrick Address Box 579 Lic. No. 212

Location of well: SW 1/4 NE 1/4 Sec. 35, T. 21 N/S, R. 61 E, in Clark County  
 or NE Corner, Gov't Lot #26

Water will be used for Domestic Total depth of well 150 feet

Size of drilled hole 12 inch Weight of casing per linear foot .1414

Thickness of casing .156 Temp. of water \_\_\_\_\_

Diameter and length of casing 8" ID 150 feet  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 19' 6"

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well April 4, 1962 Date of completion of well April 6, 1962

Type of well rig "72 Speedstar"

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Top Soil
5	10	5	Red Clay
10	13	3	Limestone
13	25	12	Red Clay
25	28	3	Gravel (Water)
28	40	12	Red Clay
40	55	15	Brown Clay
55	67	12	Limestone (Water)
67	73	6	White Clay
73	90	17	Sand (Water)
90	100	10	Red Clay
100	105	5	Gravel (Water)
105	112	7	Red Clay
112	120	8	Gravel (Water)
120	133	13	White Clay
133	142	9	Gravel & Sand (Water)
142	150	8	Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 133 to 142 ft.

Other aquifers 112-120  
100-105  
73-90  
55-67

First water at 25 feet.

Casing perforated from 80 to 145 ft.

Size of perforations 1/8" x 15"

