

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56604  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Malcolm Pike Driller S. K. McKinstry & Son

Address 204 West Owens Ave, North Las Vegas Address 1042 S. Main Lic. No. 45

Location of well: 1/4 NW 1/4 Sec. 21, T. 22 N/S, R. 2 E, in Clark County

or Lot 20 Block # 1, Tract # 1, NW 1/4 sec. 21, 20, 62 East

Water will be used for Domestic Total depth of well 75

Size of drilled hole 8" to 75 ft. Weight of casing per linear foot 24 lb.

Thickness of casing 1/4" Temp. of water \_\_\_\_\_

Diameter and length of casing 8" I.D. to 20 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 43 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well May 9, 1952 Date of completion of well May 10, 1952

Type of well rig Bucyrus Erie 24 L, Spudder

LOG OF FORMATIONS				Water-bearing Formation, Casing Perforations, Etc.
From feet	To feet	Thickness feet	Type of material	
0	4	4	Top Soil	
4	18	14	Red clay	Chief aquifer (water-bearing formation)
18	45	27	Caliche soft.	from <u>65</u> to <u>70</u> ft.
45	50	5	Caliche, hard with water	Other aquifers <u>45 to 50</u>
50	65	15	Red clay	
65	70	5	Red sand Water	
70	75	5	Red sandy clay	
				First water at <u>45</u> feet.
				Casing perforated None from _____ to _____ ft.
				Size of perforations _____

