

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56645

Rec. No. \_\_\_\_\_ 19\_\_\_\_

Well No. \_\_\_\_\_

Permit No. \_\_\_\_\_

*Do not fill in*

Owner George Roper Driller S. D. McKinney & Son

Address 714 Bridger, Las Vegas, Nev. Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: SW 1/4 NE 1/4 Sec. 21, T. 20 N/S, R. 62 E, in Clark County

or Sub 9 - Block 2 - Tract #1 Mable Manor

Water will be used for Domestic Total depth of well 90 ft.

Size of drilled hole 10" to 40 ft. 8" to 90 ft. Weight of casing per linear foot 28 lb.

Thickness of casing 5/16" Temp. of water \_\_\_\_\_

Diameter and length of casing 8" I.D. to 64 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 41 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Oct. 23, 1952 Date of completion of well Oct. 29, 1952

Type of well rig Bucyrus Erie 24 I. Boulder

### LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material |
|-----------|---------|----------------|------------------|
| 0         | 35      | 35             | Red clay         |
| 35        | 40      | 5              | White clay Hard  |
| 40        | 45      | 5              | Red sand water   |
| 45        | 65      | 20             | Red sandy clay   |
| 65        | 70      | 5              | Red sand water   |
| 70        | 85      | 15             | White clay       |
| 85        | 90      | 5              | Red sand Water   |

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 35 to 90 ft.

Other aquifers 65 to 70

---

First water at 40 feet.

Casing perforated

from None to \_\_\_\_\_ ft.

Size of perforations

