WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56690
Rec. 19
Well No. .....
Permit No. .....
Do not fill in

Owner: Bob Snyder Driller: Cribbs & Rodgers

Address: 1652 Nellis Bvld. Address: 3200 Palomino Lane Lic. No. 70 156

Location of well: ¼ ¼ Sec. 21, T 20 N/S, R 62 E, in Clark County

or 1652 Nellis Bv. Mikel Tract Lot 3 Block 2

Water will be used for: Domestic Total depth of well: 100 Ft.

Size of drilled hole: 10 in. Weight of casing per linear foot: 11 Lb.

Thickness of casing: 10 Gauge Temp. of water: .....

Diameter and length of casing: 85/8 20 ft L

(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: .....

If nonflowing well give depth of standing water from surface: 35

If flowing well describe control works: Bailer test 20 G.P.M.

(Type and size of valve, etc.)

Date of commencement of well: Aug 1954 Date of completion of well: Aug. 10

Type of well rig: Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
00	5	5	Silt and soil
5	45	40	White clay
45	47	2	gravel
47	87	40	brown clay
87	90	3	Gravel (WATER)
90	100	10	Brown clay
			100 Ft Total Depth

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 87 to 90 ft.

Other aquifers: 45 47

First water at 45 feet.

Casing perforated

from No to ..... ft.

Size of perforations

No Perf.

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
	Surface	40ft.	20	40 ft. IO Gauge well casing cemented to surface

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Charlie Cribbs
Well Driller

By S B Rodgers

License No. 70 & 156

Dated Aug 15, 1954

(Not to be filled in by Driller)