

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56698

Rec. \_\_\_\_\_ 19\_\_\_\_

Well No. \_\_\_\_\_

Permit No. \_\_\_\_\_

*Do not fill in*

Owner Allen Stewart and Bonnie Joe Inc. Driller S. R. McKinney & Son

Address Box 1871, Las Vegas Nev. Address 1012 S. Main Las Vegas Lic. No. 45

Location of well: NE 1/4 NE 1/4 Sec. 21., T. 20 N/S, R. 62E, in Clark County

or \_\_\_\_\_

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 10" to 30 ft. 8" to 100 ft. Weight of casing per linear foot 22 lb.

Thickness of casing 3/16" Temp. of water \_\_\_\_\_

Diameter and length of casing 8" O.D. to 40 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 42 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well April 1, 1953 Date of completion of well April 2, 1953

Type of well rig Bucyrus Erie 24 L. Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Sandy soil
8	24	16	Brn sandy clay
24	35	11	Gravel
35	74	39	brn sandy clay water at 55
74	97	27	white sandy clay water
97	100	3	brn sandy clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 74 to 97 ft.

Other aquifers 55 to 74

First water at 55 feet.

Casing perforated

from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations



