

X
07 1130

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 56711

Rec. 19

Well No. _____

Permit No. _____

Do not fill in

Owner ROBERT SCHNEIDER Driller LOUIS F. EVANS

Address 613 S. 10th. St. Las Vegas, Nevada Address 2020 Carroll N. Las Vegas Lic. No. 17

Location of well: S.E. 1/4 NW 1/4 Sec 36, T. 21N/S, R. 61E, in Clark County

or _____

Water will be used for Domestic Total depth of well 180 ft.

Size of drilled hole 50' 12" 130' 10" Weight of casing per linear foot 16.90 lbs.

Thickness of casing 3/16 wall Temp. of water _____

Diameter and length of casing 8 5/8" O.D. 180'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 14 ft.

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well Nov. 26, 1960 Date of completion of well Dec. 13, 1960

Type of well rig Keystone

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	sandy clay
6	9	3	gravel
9	10	1	gyp
10	14	4	clay & gravel
14	15	1	gyp
15	24	9	clay & gravel
24	25	1	gyp
25	33	8	gravel (water)
33	39	6	brown sandy clay
39	42	3	gravel (water)
42	68	26	brown clay & gravel
68	71	3	gravel water
71	97	26	brown clay & gravel
97	99	2	gravel (water)
99	114	15	brown clay
114	115	1	gravel (water)
115	122	7	brown clay & gravel (water)
122	123	1	gravel (water)
123	142	19	red clay
142	155	13	red clay & gravel
155	159	4	gravel (water)
159	161	2	red clay & gravel
161	169	8	gravel (water)
169	180	11	red clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 161 to 169 ft.

Other aquifers 68 to 71
97 to 99 114 to 123
155 to 159

First water at 29 feet.

Casing perforated

from 60 to 180 ft.

Size of perforations

1/4" wide 6" long

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 5/8"	0	180	180	gravel packed 130 ft. from 50 ft. to 180 ft. 4 yds. cemented 50 ft. from 0 to 50 ft. 2 yds.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Louis F. Evans
Well Driller

By Louis F. Evans

License No. 117

Dated Dec. 29, 19 60

(Not to be filled in by Driller)
