WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56726
Rec. ..... 19....
Well No. .....
Permit No. .....
Do not fill in

Owner John Tatar Driller S.R. McKinney & Son

Address Genl Del Las Vegas Address 1042 So. Main Lic. No. 45

Location of well: SW. ¼ NE ¼ Sec. 21, T. 20 N/S, R. 62 E, in Clark County

or East College

Water will be used for Domestic Total depth of well 75

Size of drilled hole 8" Weight of casing per linear foot 28#

Thickness of casing 5/16 wall Temp. of water .....

Diameter and length of casing 40 feet 8 5/8" O.D.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface 42'

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well Dec 15 Date of completion of well Dec 17/52

Type of well rig Bucyrus Erie Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Topsoil
2	15	13	Brown Clay
15	18	3	Sandy brown Clay
18	26	8	Gravel - dry
26	40	14	White Clay
40	65	25	red sandy Clay
65	67	2	red Sand (Water)
67	72	5	White Clay
72	75	3	White Sand (Water)

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 65 to 67 ft.

Other aquifers 72 - 75

First water at 67 feet.

Casing perforated

from None to ..... ft.

Size of perforations

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 5/8	0	40	40	Cemented - 1 yd. grout.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailing test - 35 g.p.m. to 55'
13 ft drawdown.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. P. McKinney
Well Driller

By.....

License No. 45

Dated Dec 23, 1954

(Not to be filled in by Driller)