

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56734  
 Rec. No. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Robert Taylor & Bonnie Joe Inc Driller S. R. McKinney & Son  
 Address 2 Hanks Motor Shop, 13, West Charleston 1042 S. Main Lic. No. 45  
 Location of well: NE 1/4 Sec. 21, T. 20N/S, R. 62E, in Clark County  
 or S. E. corner of Meikle Lane and Christy Lane  
 Water will be used for Domestic Total depth of well 100  
 Size of drilled hole 10" to 35 ft, 8" to 100 Weight of casing per linear foot 18 lb.  
 Thickness of casing 3/16" Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" O.D. to 40 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 40 ft.  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well March 16, 1953 Date of completion of well March 17, 1953  
 Type of well rig Bucyrus Erie 24-B, Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	4	4	topsoil	
4	25	21	hard brown sandy clay	
25	48	23	brown sandy clay	
48	56	8	soft white clay water	Chief aquifer (water-bearing formation) from <u>80</u> to <u>90</u> ft.
56	80	24	brown sandy clay	Other aquifers <u>48 to 56</u>
80	90	10	light brown clay water	
90	100	10	white sandy clay	
				First water at <u>48</u> feet.
				Casing perforated from <u>None</u> to _____ ft.
				Size of perforations _____

