

WELL LOG AND REPORT TO THE STATE ENGINEER  
OF NEVADA

DEVELOPING JOB

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 56740  
 Rec. No. 19  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Do not fill in.

Owner Don Trenkle Driller S. R. McKinney & Sons, Inc.

Address 1648 Betty Lane Las Vegas Address 1042 S Main Las Vegas No. 45

Location of well: SW 1/4 SW 1/4 Sec. 21, T. 20N/S, R. 62E, in Clark County

Water will be used for Domestic Total depth of well 200 ft.

Size of drilled hole 8" to 200 ft. Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water \_\_\_\_\_

Diameter and length of casing 6 5/8" from 0 to 200 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 53 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 7-25-66 Date of completion of well 7-27-66

Type of well rig Bucyrus Erie 22 W Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
100	120	20	clay
120	135	15	clay and gravel water
135	150	15	clay
150	165	15	graveley clay water
165	170	5	clay
170	200	30	graveley clay water

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)  
 from 170 to 200 ft.

Other aquifers 150 to 165  
120 to 135

First water at 120 feet.

Casing perforated  
 from 60 to 200 ft.

Size of perforations  
3/16" X 10"

