


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56745  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_



Owner Robert D. Wagner Driller Effinger Drill & Pump Serv.

Address 1652 Betty Lane Address Box 589 Lic. No. 212

Location of well: SE 1/4 SW 1/4 Sec. 21, T20N/S, R62E, in Clark County  
 or 1652 Betty Lane

Water will be used for Domestic Total depth of well 120 feet

Size of drilled hole 12 Inch Weight of casing per linear foot 12.06

Thickness of casing 10 Gauge Temp. of water \_\_\_\_\_

Diameter and length of casing 8"OD 120 feet  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 40' 2" from top of casing

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well October 27, 1958 Date of completion of well October 29, 1958

Type of well rig "71 Speed Star"

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	Yellow Clay
4	7	3	Limestone
7	23	16	Yellow Clay
23	25	2	Limestone
25	47	22	Yellow Clay
47	55	8	Gravel (Water)
55	83	27	Gravel & Decomposed Limestone (W)
83	91	8	White Clay
91	93	2	Red Clay
93	108	15	Limestone (Water)
108	120	12	White & Yellow Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 93 to 108 ft.

Other aquifers 47-83

First water at 47 feet.

Casing perforated from 60 to 120 ft.

Size of perforations 1/8" X 15"



