

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56760

Rec. \_\_\_\_\_ 19\_\_

Well No. \_\_\_\_\_

Permit No. \_\_\_\_\_

*Do not fill in*

Owner Clint Whitaker Driller S. R. McKinney & Son

Address Box 1871, Las Vegas, Nev. Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: NW 1/4 SW 1/4 Sec. 21., T. 20 N/S, R. 62 E, in Clark County

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 12" to 50 ft., 10" to 100 Weight of casing per linear foot 10 guage

Thickness of casing 10 guage Temp. of water \_\_\_\_\_

Diameter and length of casing 8" I.D. to 100 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 40 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Jan. 12, 1955 Date of completion of well Jan 13, 1955

Type of well rig Bucyrus Erie 24 L, Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	28	28	brown clay
28	39	11	sand and gravel
39	45	6	brown clay
45	70	25	gravel water
70	84	14	white clay
84	87	3	white sand water
87	96	9	white clay
96	100	4	white sand water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 96 to 100 ft.

Other aquifers 84 to 87

50 to 70

First water at 45 feet.

Casing perforated

from 50 to 100 ft.

Size of perforations

3/16" X 10"



