

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. **56778**  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

*Greenwood*

Owner Ross A. Harris Driller S. R. McKinney & Son

Address 824 S. Orange Grove Ave. L. A. 36 Address 1042 S. Main Las Vegas Lic. No. 45  
Calif.

Location of well: SE 1/4, SE 1/4 Sec. 4, T. 22N/S, R. 63E, in Clark County

Water will be used for Domestic Total depth of well 300 ft.

Size of drilled hole 12" to 50 ft, 10" to 300 Weight of casing per linear foot 24 lb.

Thickness of casing 1/4" Temp. of water \_\_\_\_\_

Diameter and length of casing 8" I.D. to 300ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 235 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Feb. 1, 1956 Date of completion of well Feb. 14, 1956

Type of well rig Bucyrus Erie 24 L, Soudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	gravel
5	185	180	cemented gravel
185	235	50	cemented gravel and red gravel
235	250	15	red and grey cemented gravel carrying water
250	260	10	red gravel and sand water
260	277	17	red gravel
277	300	23	red gravel and sand water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 277 to 300 ft.

Other aquifers 250 to 260

235 to 260

First water at 235 feet.

Casing perforated

from 260 to 300 ft.

Size of perforations

3/16" x 10"

