Log No. 56781
Rec. 6/20 1955
Well No.
Permit No.
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Owner Robt. J. or Elsie P. Sendlein Driller Robert J. Sendlein

Address 8 Lincoln St. Henderson Nev. Address 8 Lincoln Henderson Lic. No. 130

Location of well: ¼ ¼ Sec. 22 T. 22 S, R. 63 E, in Clark County

or Henderson Nev. lot #20

Water will be used for Domestic Total depth of well 280

Size of drilled hole 12 inches Weight of casing per linear foot Approximate 5½

Thickness of casing 10 gauge Temp. of water cool or avagre

Diameter and length of casing 8" inches 20 ft. lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 75 ft.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well May 15, 55 Date of completion of well June 19th, 55

Type of well rig rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
1	147	147	Pea gravel & loose rocks
148	155	8	sandy clay
156	162	7	loose rocks
163	167	5	fine sand
168	171	4	sandy clay
172	180	9	gravel & rocks
181	184	4	hard clay or clochey
185	192	8	boulders
193	198	6	coarse sand & gravel
199	201	3	clay
202	212	11	sand
213	228	16	gravel, sand & rocks
229	232	4	sandy clay
233	247	15	loose boulders
248	257	10	coarse sand & rocks
258	260	3	clay
261	269	9	loose rocks
270	273	4	clay
274	278	5	loose rocks
279	280	2	clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 247 to 280 ft.

Other aquifers Some water, very little 162 to 247

First water at 155 feet.

Casing perforated

from 220 to 280 ft.

Size of perforations

1/8 kerfs

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8	1	280	280	~~2y~~ 2 yds pea gravel 1 3/4 yds grout

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Used air comp. to surge & pump well. Cap. of comp. 20 gals min. but had a lot more water. Water very cool, and soft water

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Robert J. Sendlein
Well Driller

By Robert J. Sendlein

License No. 130

Dated June 20th, 1955

(Not to be filled in by Driller)