

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 56948  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Bonnie Jo Inc. and Mr. Bishop Driller S. R. McKinney & Son

Address Box 1871, Las Vegas, Nevada Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: NE 1/4 SW 1/4 Sec 28, T20 N/S, R62 E, in Clark County

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole: 12" to 50 ft, 10" to 100 Weight of casing per linear foot: 10 guage

Thickness of casing: 10 guage Temp. of water \_\_\_\_\_

Diameter and length of casing: 8" I.D. to 100 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. \_\_\_\_\_

If nonflowing well give depth of standing water from surface: 55 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well: Jan 26, 1955 Date of completion of well: Jan 27, 1955

Type of well rig: 71 Speed Star Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	15	15	sandy clay
15	45	30	soft sandy clay
45	80	35	sand and graveley clay water
80	100	20	sand and gravel water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 80 to 100 ft.

Other aquifers: 45 to 80

First water at 45 feet.

Casing perforated

from 50 to 100 ft.

Size of perforations

3/16" X 10"



