

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56960
 Rec. No. _____ 19____
 Well No. _____
 Permit No. _____
Do not fill in

Owner Chet Brumley Driller S. R. McKinney & Son

Address 1200 Nellis Blvd. Las Vegas Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: SW 1/4 NW 1/4 Sec. 28., T.20 N/S, R.62 E, in Clark County
or _____

Water will be used for Domestic Total depth of well ~~100~~ 100 ft.

Size of drilled hole 12" to 50 ft., 10" to 100 Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water _____

Diameter and length of casing 8" I.D. to 100 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 29 ft.

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well March 28, 1956 Date of completion of well March 29, 1956

Type of well rig Bucyrus Erie 24 L. Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	30	30	brown clay
30	34	4	brown sand water
34	40	6	white clay
40	60	20	gravel water
60	65	5	red sandy clay
65	70	5	red sand water
70	85	15	white clay
85	87	2	white sand water
87	95	8	white clay
95	100	5	white sand water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 95 to 100 ft.

Other aquifers 85 to 87,

65 to 70, 50 to 60

First water at 30 feet.

Casing perforated

from 60 to 100 ft.

Size of perforations

3/16" X 10"



