

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

56988

Reg. No. \_\_\_\_\_  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Prentis Dement Driller S. R. McKinley & Son

Address East College, Las Vegas Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: NW 1/4 NW 1/4 Sec. 28, T. 20N/S, R. 62E, in Clark County \_\_\_\_\_

or \_\_\_\_\_

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 10" to 30 ft, 8" to 100 ft Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water \_\_\_\_\_

Diameter and length of casing 9" O.D. to 40 ft.  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 35 ft

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well Dec 14, 1953 Date of completion of well Dec 14, 1953

Type of well rig Bucyrus Erke 24 L, Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	topsoil
6	35	29	Brown clay
35	45	10	brown sand water
45	65	20	brown sandy clay
65	75	10	brown sand water
75	85	10	white clay
85	95	10	white sand water
95	100	5	white clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 85 to 90 ft.

Other aquifers 65 to 75

First water at 35 feet.

Casing perforated

from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations



