

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57011
 Rec. No. _____ 19____
 Well No. _____
 Perm. No. _____
Do not fill in



Owner Golden West & Hamill Driller S. E. McKinney & Son

Address Box 1871, Las Vegas Address 1042 S. Main Lic. No. 45

Location of well: NW 1/4 W 1/4 Sec. 28., T. 20N/S, R. 62E, in Clark County

or _____

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 10" to 30 ft. 8" to 100 ft. Weight of casing per linear foot 18 lb.

Thickness of casing 3/16" Temp. of water _____

Diameter and length of casing 8" O.D. to 40 ft.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 30 ft.

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well June 18, 1953 Date of completion of well June 18, 1953

Type of well rig Bucyrus Erie 24 L. Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	Brown sandy clay
6	30	24	brown clay
30	40	10	brown sand water
40	60	20	white clay
60	65	5	white sand water
65	85	20	white sandy clay
85	90	5	white sand water
90	100	10	white clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 85 to 90 ft.

Other aquifers 60 to 65

30 to 40

First water at 30 feet.

Casing perforated

from _____ to _____ ft.

Size of perforations



