Log No. 57123
Rec. 19
Well No. .....
Permit No. .....
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: BUREN HOFFMAN Driller: LOUIS F. EVANS

Address: 1421 BETTY LANE LAS VEGAS, NEVADA Address: 2012 CARROLL N. LAS VEGAS Lic. No. 117

Location of well: N.W¼ NW ¼ Sec. 28, T. 20 N/S, R. 62 E, in CLARK County

or .....

Water will be used for: DOMESTIC Total depth of well: 200 ft.

Size of drilled hole: 50' 12" 150' 10" Weight of casing per linear foot: 12.15 lbs.

Thickness of casing: 10 ga. Temp. of water .....

Diameter and length of casing: 8 5/8" O.D. 200'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface: 60 ft.

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well: July 28, 1966 Date of completion of well: Aug. 10, 1966

Type of well rig: Keystone cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	soil
3	15	12	brown clay
15	25	10	gray clay
25	50	25	sandy gray clay
50	80	30	white clay
80	90	10	white clay (water)
90	100	10	white sandy clay (water)
100	120	20	brown sandy clay
120	135	15	white sandy clay
135	145	10	white sandy clay (water)
145	160	15	brown clay
160	170	10	white clay (water)
170	180	10	brown clay
180	190	10	red clay
190	195	5	sandy clay (water)
195	200	5	red clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 160 to 170 ft.

Other aquifers: 80 to 100

135 to 145 190 to 195

First water at 80 feet.

Casing perforated

from 100 to 200 ft.

Size of perforations

¼" wide 6" long

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

RECEIVED
SEP 12 1966
DIV. OF WATER RESOURCES
BRANCH OFFICE
LAS VEGAS, NEVADA

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 5/8"	0	200	200	gravel packed 150 ft,from 50 ft. to 200 ft. 1¼ yds. gravel cemented 50 ft. from 0 to 50 ft, 1 3/4 yds.cement

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Louis F. Evans
Well Driller

By LOUIS F. EVANS

License No. 117

Dated Sept. 8, 19 66

(Not to be filled in by Driller)