

WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA

Ralph Draper

Log No. 57166  
 Rec. No. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Thomas Mann Driller S. R. McKinney & Son

Address Box 1871, Las Vegas, Nev. Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: NE 1/4 NW 1/4 Sec. 28., T. 20N/S, R. 62E, in Clark County

or Lot 25, Block 2, Tract 4, Meikle Manor

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 10" to 30 ft 8" to 100 Weight of casing per linear foot 12 guage

Thickness of casing 12 guage Temp. of water \_\_\_\_\_

Diameter and length of casing 8" O.D. to 40 ft  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 35 ft

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well March 2, 1954 Date of completion of well March 2, 1954

Type of well rig Bucyrus Erie 24 L, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	35	35	brown clay
35	40	5	brown sand water
40	55	15	brown clay
55	60	5	brown sand water
60	75	15	white clay
75	80	5	white sand water
80	95	15	white clay
95	100	5	white sand water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 95 to 100 ft.

Other aquifers 75 to 80

55 to 60,

First water at 35 feet.

Casing perforated

from none to \_\_\_\_\_ ft.

Size of perforations



