

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57180

Rec. 19

Well No. _____

Permit No. _____

Do not fill in

Owner Golden West Corp. & H. F. Murphy Driller S.R. McKinney & Son

Address P.O. Box 1871, Las Vegas, Nevada Address 1042 So. Main, L.V. Lic. No 45

Location of well: SE $\frac{1}{4}$ NW $\frac{1}{4}$ Sec. 28, T20 N/S, R. 62E, in Clark County _____
or _____

Water will be used for Domestic Total depth of well 100'

Size of drilled hole 12" to 50', 10" to 100 Weight of casing per linear foot 10 Guage

Thickness of casing 10 Guage Temp. of water _____

Diameter and length of casing Increasing 8" I.D. to 100'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 28'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well June 10, 1955 Date of completion of well June 10, 1955

Type of well rig Bucyrus Erie 24L, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Topsoil
8	35	27	Brown clay
35	38	3	Brown sand water
38	55	17	Brown sandy clay
55	64	9	White clay
64	76	12	White sand water
76	85	9	White clay
85	92	7	White sand water
92	100	8	White clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 85 to 92 ft.
64' to 76'

Other aquifers 35' to 38'

First water at 35 feet.

Casing perforated
from 50 to 100 ft.

Size of perforations
3/16" X 10"



