

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57201
 Re. No. 19
 Well No. _____
 Permit No. _____
Do not fill in



Owner Meikle & Roxborough Driller S. R. McKinney & Son
 Address 90 Meikle East Ave. Address 1042 S. Main Las Vegas Lic. No. 45
 Location of well: N 1/4, 10 1/4 Sec. 28, T. 20 N/S, R. 6 E, in Clark County
 or _____

Water will be used for Domestic Total depth of well 75 ft.

Size of drilled hole 12" to 40 ft. 8" to 60 ft. Weight of casing per linear foot 20 lb.

Thickness of casing 3/16" Temp. of water _____

Diameter and length of casing 8" I.D. to 60 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 30 ft.

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well Jan 8, 1953 Date of completion of well Jan 9, 1953

Type of well rig Bucyrus Erie 24 L, Sander

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	Topsoil
4	30	26	red clay
30	35	5	red sand water
35	40	5	red sandy clay
40	50	10	red sand and gravel water
50	55	5	sand and gravel water
55	65	10	white clay
65	70	5	white sand water
70	75	5	white clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 65 to 70 ft.

Other aquifers 50 to 55

First water at 30 feet.

Casing perforated

from 32 to 60 ft.

Size of perforations

3/16" X 10"



