

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57206  
 Rec. 7/22 1954  
 Well No. \_\_\_\_\_  
 Permit No. Do-4  
*Do not fill in*



Owner St. Thomas Episcopal Church Driller S.R. McKinney & Son

Address East College & Bledsoe Lane Address 1042 S. Main L.V. N. Lic. No. 45

Location of well: NE 1/4 NW 1/4 Sec. 28., T. 20 N/S, R. 62 E, in Clark County County  
 or \_\_\_\_\_

Water will be used for Domestic use Total depth of well 100

Size of drilled hole 10" to 45', 8" to 100' Weight of casing per linear foot 10 gage

Thickness of casing 10 guage Temp. of water \_\_\_\_\_

Diameter and length of casing 8" I.D. 60'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 35'

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well June-30, 54 Date of completion of well June-30, 54

Type of well rig Bucyrus Ere 24 L, Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	41	41	Brown clay
41	44	3	brown sand water
44	60	16	brown sandy clay
60	61	1	white sand water
61	68	7	white sandy clay
68	71	3	brown sand water
71	88	17	brown sandy clay
88	92	4	sand stone water
92	100	8	white sandy clay

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 88 to 92 ft.

Other aquifers 68 to 71  
60 to 61

---

First water at 41 feet.

Casing perforated  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations  
None

