

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57267  
 Rec. No. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Clint Whitaker ~~Richard~~ Driller S. R. McKinney & Son

Address Box 1871, Las Vegas, Nevada Address 1042 S. Main Las Vegas B.C. No. 45

Location of well: NE 1/4 NW 1/4 Sec 28, T20N/S, R67E, in Clark County

or \_\_\_\_\_

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 12" to 55 ft., 10" to 100 Weight of casing per linear foot 10 guage

Thickness of casing 10 guage Temp. of water \_\_\_\_\_

Diameter and length of casing 8" I.D. to 100 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 34 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well June 4, 1956 Date of completion of well June 5, 1956

Type of well rig Bucyrus Erie 24 L, Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	<del>5</del> 5	topsoil
5	28	23	brown clay
28	29	1	gravel
29	38	9	brown clay
38	41	3	brown sand water
41	62	21	white clay
62	67	5	white sand water
67	78	11	brown clay
78	89	11	brown sand water
89	100	11	brown clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 78 to 89 ft.

Other aquifers 62 to 67

First water at 38 feet.

Casing perforated

from 60 to 100 ft.

Size of perforations

3/16" X 10"



