


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 57274  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_



Do not fill in.

Owner Cecil Womack Driller Patrick Thompson

Address 5019 E. Owens L.V. Address Las Vegas, Nevada Lic. No. 192

Location of well: SE 1/4 NE 1/4 Sec. 29, T. 20 N/S, R62 E, in Clark County  
 or 5019 E. Owens Las Vegas, Nevada

Water will be used for Domestic Total depth of well 120'

Size of drilled hole 12" to 50' - 10" 50-120' Weight of casing per linear foot 12#

Thickness of casing 10 Gauge Temp. of water Cool

Diameter and length of casing Diameter - 8-5/8" Length - 121'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 52'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 5-8-64 Date of completion of well 5-8-64

Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	48	48	Brown Clay
48	50	2'	Lime Shell
50	120	70	White Clay with Streaks of Lime.

#### Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)  
 from 52 to 120 ft.

Other aquifers None

First water at 52' feet.

Casing perforated  
 from 60 to 120 ft.

Size of perforations  
3/16 x 12 4 Rows



