

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57404
 Rec. _____ 19____
 Well No. _____
 Permit No. _____
Do not fill in

Owner John Fry Driller S. R. McKinley & Son

Address P.O. Box 3559, North Las Vegas Address 1042 S. Main Las Vegas Sec. No. 45

Location of well: SE¹/₄ SE¹/₄ Sec. 29, T20 N/S, R62 E, in Clark County

or _____

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 12" to 60 ft., 10" to 80 ft. Weight of casing per linear foot 10 guage

Thickness of casing 10 guage Temp. of water _____

Diameter and length of casing 8" I.D. to 100 ft.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 25 ft.

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well March 12, 1957 Date of completion of well March 13, 1957

Type of well rig Bucyrus Erie 24 L Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	35	35	brown clay
35	40	5	brown sand water
40	51	11	brown clay
51	55	4	gravel and sand water
55	64	9	grey clay
64	70	6	brown sand water
70	85	15	brown sandy clay
85	90	5	brown sand water
90	93	3	hard brown clay
93	100	7	brown sand water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 93 to 100 ft.

Other aquifers 85 to 90
64 to 70

First water at 35 feet.

Casing perforated
STATE ENGINEER

from 60 to 100 ft.

APR 11 1957

Size of perforations
3/16" X 10"

