

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 57406
 Rec. _____ 19____
 Well No. _____
 Permit No. _____
 Do not fill in

Owner R. Gaillard Driller S.R. McKinney & Sons, Inc.

Address 1400 Lamb Lane Address 1042 So. Main Lic. No. 45

Location of well: NW 1/4 NW 1/4 Sec. 29, T. 20N/S, R. 62E, in Clark County

Water will be used for Domestic Use Total depth of well 300'

Size of drilled hole 12" to 50', 10" to 300' Weight of casing per linear foot 3/16"

Thickness of casing 3/16" Temp. of water _____

Diameter and length of casing 8" ID from 0' to 300'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 45'

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well 7/17/62 Date of completion of well 7/21/62

Type of well rig Bucyrus Erie 22W

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	8	8	clay	
8	21	13	gravel	Chief aquifer (water-bearing formation)
21	40	19	gravely clay	
40	60	20	brown clay	from <u>260</u> to <u>300</u> ft.
60	70	10	clay	
70	75	5	gravely clay	Other aquifers <u>93 to 95'</u>
75	93	18	clay	<u>102 to 104'</u>
93	95	2	gravel (water)	<u>165 to 175'</u>
95	102	7	brown gritty clay	<u>175 to 260'</u>
102	104	2	gravel (water)	
104	165	61	brown clay & gravel streaks	
165	175	10	brown clay & gravel streaks (water)	
175	260	85	brown sticky clay with hard streaks (water)	First water at _____ feet.
260	300	40	blue & brown clay with hard streaks (water)	Casing perforated from <u>74</u> to <u>300</u> ft.
				Size of perforations <u>3/16" X 10"</u>



