

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57429  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Pat Kennedy Driller McGARVIE PLUMBING & WELDING

Address 1990 Fremont Address Las Vegas, Nevada Lic. No. 132

Location of well:  $\frac{1}{4}$  Sec. 29, T20N/S, R62E, in \_\_\_\_\_ County  
 or At Hernando's Highway on Nellis Boulevard

Water will be used for domestic Total depth of well 120'

Size of drilled hole 8" Weight of casing per linear foot \_\_\_\_\_

Thickness of casing 8 x 10 guage Temp. of water \_\_\_\_\_

Diameter and length of casing 8" x 120'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 34'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well \_\_\_\_\_ Date of completion of well \_\_\_\_\_

Type of well rig cable

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	34	34	white clay
34	70	36	red clay
70	85	15	white clay
85	120	35	red sandy clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 34 to 120 ft.

Other aquifers \_\_\_\_\_

First water at 34' feet.

Casing perforated

from 80 to 120 ft.

Size of perforations

1/8" x 6" slots



