

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57509
 Rec. 19
 Well No. _____
 Permit No. _____
Do not fill in

Owner Monroe P. Ashins Driller Patrick H. Thompson

Address 1400 No. Genesee, Hollywood 46, California. Address 217 So 26th St. LV, Nev. Lic. No. 192

Location of well: NE 1/4, SE 1/4 Sec. 28, T22-N/S, R61-E, in Clark County

or NE 1/4, SE 1/4, NW 1/4, SW 1/4 OF SAID SECTION

Water will be used for Domestic Total depth of well 180'

Size of drilled hole 12" to 50' - 10" from 50' to 180' Weight of casing per linear foot 12.2

Thickness of casing 10 gauge Temp. of water cold

Diameter and length of casing 8" Dia. 181' length
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 95'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well Aug. 23, 1955 Date of completion of well Aug. 30, 1955

Type of well rig Star Snudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Sand and gravel
10	95	85	Cemented gravel
95	115	20	Gravel
115	147	32	Cemented gravel
147	155	8	Red clay
155	158	3	Gravel
158	167	9	Red clay
167	180	13	Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 167 to 180 ft.

Other aquifers 95' - 105'

155' - 158'

First water at 115 feet.

Casing perforated

from 120 to 180 ft.

Size of perforations

3/16 x 12 - 4 PWS

